

Waterite



Solutions
Limpides

WATERITE TECHNOLOGIES, INC.

3-75 Meridian Drive

Winnipeg, MB

Canada R2R 2V9

PHONE: (204) 786-1604

FAX: (204) 783-1599

Email: waterite@waterite.com

Website: www.waterite.com

Solutions Limpides Inc.

www.solutionslimpides.com

cel.: 1.450.531.9756, mob.

tel.: toll free: 1.855.378.4011, sans frais

VECTAMAXX™ RSL COMMERCIAL

REVERSE OSMOSIS SYSTEMS

A. GENERAL SPECIFICATIONS

TYPE: Extra Low pressure RO, spiral wound membrane(s) in series, recirculation loop

VOLTAGE: 230VAC/60hz (other voltages available on request)

SERVICE AMPS:	230VAC
RSL2400	6.4
RSL4800	6.4
RSL7200	8.1
RSL9600	12.0

FEED WATER PRESSURE: 40 psi minimum, 65 psi maximum

FEED WATER TEMP: 35° C maximum

B. MATERIAL SPECIFICATIONS:

FRAME COLOUR: White powder coat

FRAME MATERIAL: Mild steel square tubular, c/w leveling feet

FRAME DIMENSIONS:

Height 50" (127cm)

Width 31" (79cm)

Depth 24.0" (62cm)

OPERATING PRESSURE: 130 psi (9.1 bar) for RSL 2400, 4800 and 9600,

140 psi (9.9 bar) for RSL 7200

SPEC RO-SYS-002R5

September2010